


Dummy coupling



P= Stück / Normpackung // Pieces/ standard pack

Material: **Standardversion / Standard version**

Kupplungsgrundkörper: Messing / Coupler Body: Brass
 Hülse: Messing / Sleeve: Brass
 Ventil: Messing / Valve: Brass
 Feder: Edelstahl / Spring: Stainless Steel
 Sprengring: Edelstahl / Locking O-Ring: Stainless Steel
 Kugeln: Edelstahl V-/ Balls: Stainless Steel

Betriebsdruck / Working pressure: p (bar)

Optionen / Options:

Verchromt / Chrome plated – Index: -Cr
 Vernickelt / Nickel plated – Index: -Ni
 Edelstahl / Stainless Steel – Index: -S

Bei optionaler Bestellung bitte Kennbuchstaben hinzufügen:
 For optional orders please add the options index end of the order no.:
 (Beispiel/example: K7075-d4-Cr)

p (bar)	d3 (mm)	L1 (mm)	P	d4 (mm)	Bestellnummer Order Number
0 - 10	18	34	10	9	K7075-09
0 - 15	23	40		13	K7075-13

Dauertemperatur / Long-term service temperature

K7075	Standard	
	Medium	Max. C°
	Öl / Oil	160
	Wasser / Water	120

K7076	Hochtemperatur High temperature	
	Medium	Max. C°
	Öl / Oil	200
	Wasser / Water	160

K7077	Höchsttemperatur High of temperature	
	Medium	Max. C°
	Öl / Oil	300
	Wasser / Water	250